	Application No.	Applicant(s)
Notice of Allowability	10/043,127	ABE, NOBUAKI
	Examiner	Art Unit
	Tuan V Ho	2615
The MAILING DATE of this communication appears on the cover sheet with the correspondence address All claims being allowable, PROSECUTION ON THE MERITS IS (OR REMAINS) CLOSED in this application. If not included herewith (or previously mailed), a Notice of Allowance (PTOL-85) or other appropriate communication will be mailed in due course. THIS NOTICE OF ALLOWABILITY IS NOT A GRANT OF PATENT RIGHTS. This application is subject to withdrawal from issue at the initiative of the Office or upon petition by the applicant. See 37 CFR 1.313 and MPEP 1308.  1. This communication is responsive to  2. The allowed claim(s) is/are 1-25.  3. The drawings filed on 1/4/2002 are accepted by the Examiner.  4. Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).  a) All b) Some* c) None of the:  1. Certified copies of the priority documents have been received.  2. Certified copies of the priority documents have been received in Application No  3. Copies of the certified copies of the priority documents have been received in this national stage application from the		
International Bureau (PCT Rule 17.2(a)).  * Certified copies not received:  Applicant has THREE MONTHS FROM THE "MAILING DATE" of this communication to file a reply complying with the requirements noted below. Failure to timely comply will result in ABANDONMENT of this application.		
<ul> <li>THIS THREE-MONTH PERIOD IS NOT EXTENDABLE.</li> <li>5. A SUBSTITUTE OATH OR DECLARATION must be submitted. Note the attached EXAMINER'S AMENDMENT or NOTICE OF INFORMAL PATENT APPLICATION (PTO-152) which gives reason(s) why the oath or declaration is deficient.</li> </ul>		
<ul> <li>6. CORRECTED DRAWINGS (as "replacement sheets") must be submitted.</li> <li>(a) including changes required by the Notice of Draftsperson's Patent Drawing Review (PTO-948) attached</li> <li>1) hereto or 2) to Paper No./Mail Date</li> <li>(b) including changes required by the attached Examiner's Amendment / Comment or in the Office action of Paper No./Mail Date</li> <li>Identifying indicia such as the application number (see 37 CFR 1.84(c)) should be written on the drawings in the front (not the back) of each sheet. Replacement sheet(s) should be labeled as such in the header according to 37 CFR 1.121(d).</li> <li>7. DEPOSIT OF and/or INFORMATION about the deposit of BIOLOGICAL MATERIAL must be submitted. Note the attached Examiner's comment regarding REQUIREMENT FOR THE DEPOSIT OF BIOLOGICAL MATERIAL.</li> </ul>		
Attachment(s)  1. Notice of References Cited (PTO-892)  2. Notice of Draftperson's Patent Drawing Review (PTO-948)  3. Information Disclosure Statements (PTO-1449 or PTO/SB/0 Paper No./Mail Date  4. Examiner's Comment Regarding Requirement for Deposit of Biological Material	6. ⊠ Interview Summary Paper No./Mail Da 98), 7. ⊠ Examiner's Amenda	te .

Application/Control Number: 10/043,127

Art Unit: 2615

1. An examiner's amendment to the record appears below. Should the changes and/or additions be unacceptable to applicant, an amendment may be filed as provided by 37 CFR 1.312. To ensure consideration of such an amendment, it MUST be submitted no later than the payment of the issue fee.

Page : 1

Authorization for this examiner's amendment was given in a telephone interview with Mr. Piepz on 1/6/2005.

The application has been amended as follows:

10

15

20

(CULBENTLY AMENDED)

1. An image interpolating device comprising:

a color filter having a first row, in which red (R) and green (G) color filter elements are alternately aligned in the horizontal direction, and a second row, in which G and blue (B) color filter elements are alternately aligned in the horizontal direction, said second row being adjacent to the upper or lower side of said first row;

an imaging device that generates first R, G, and B-signals which are pixel signals corresponding to said color filter elements;

a pattern-setting processor that extracts images belonging to a first pattern, in which a pixel having said first R-signal is positioned at the upper-left corner of a 2 x 2 pixel matrix, a second pattern, in which a pixel having said first G-signal is positioned at the upper-right corner of said 2 x 2 pixel matrix, a third pattern, in which a pixel having said first G-signal is positioned at the lower-left corner of said 2 x 2 pixel matrix, and a fourth pattern, in which a pixel having said first B-signal is positioned at the lower-right corner of said 2 x 2 pixel matrix, from said first R, G, and B-signals generated by said imaging device;

a G-interpolation processor that, regarding first and fourth objective pixels contained in said images belonging to said first and fourth patterns, obtains a second G-signal by utilizing said first G-signals of pixels adjacent to said first or fourth objective pixel;

an R/B-interpolation processor that, regarding second and third

5

10

15

20

objective pixels contained in said images belonging to said second and third patterns, obtains second R and B-signals by utilizing said first R and B-signals of pixels adjacent to said second and third objective pixels;

a B-interpolation processor that extracts a first similar pixel which has the closest luminance value to that of said first objective pixel, from pixels adjacent to said first objective pixel, and obtains a third B-signal based on first information of said first similar pixel; and

an R-interpolation processor that extracts a second similar pixel which has the closest luminance value to that of said fourth objective pixel, from pixels adjacent to said fourth objective pixel, and obtains a third R-signal based on second information of said second similar pixel.

2. A device according to claim 1, wherein said first information comprises a luminance value and a color difference signal Cb of said first similar pixel, and said second information comprises a luminance value and a color difference signal Cr of said second similar pixel.

3. A device according to claim 1, wherein said first information comprises color difference signals Cb and Cr, and said second information comprises color difference signals Cb and Cr.

4. A device according to claim 1, wherein said pixels, which are adjacent to said first and fourth objective pixels and which are utilized in said G-interpolation processor, are contained in said images belonging to said second and third patterns.

(ORIGINAL)

5. A device according to claim 1, wherein said pixels, which are adjacent to said second and third objective pixels and which are utilized in said R/B-interpolation processor, are contained in said images belonging to said first and fourth patterns.

(COMENICY DILENDED)

- 6. A device according to claim 1, wherein said pixels, which are adjacent to said first and fourth objective pixels and which are utilized in both said B-interpolation processor and said R-interpolation processor, are contained in said images belonging to said second and third patterns.
- 7. A device according to claim 1, wherein said B-interpolation \*\*
  10 processor and said R-interpolation processor respectively extract said first and second similar pixels, using said first G-signals of said pixels adjacent to said first and fourth objective pixels.

(WILLEWTLY ALLEW TED)

- 8. A device according to claim 2, wherein said B-interpolation by processor obtains said third B-signal, on the assumption that said color difference signal Cb of said first objective pixel is equal to said color difference signal Cb of said first similar pixel.
  - 9. A device according to claim 2, wherein said R-interpolation processor obtains said third R-signal, on the assumption that said color difference signal Cr of said fourth objective pixel is equal to said color
- 20 difference signal Cr of said second similar pixel.
  (ωνιξωτιγ Αμτώνου)
  - 10. A device according to claim 2, wherein said B-interpolation processor obtains said third B-signal, using said color difference signal Cb and a modified luminance value which is obtained by multiplying said

luminance value by a ratio of sald second G-signal of said first objective pixel and said first G-signal of said first similar pixel.

((MPATENILY AMENDED)

11. A device according to claim 10, wherein said B-interpolation processor obtains said third B-signal, according to the following formula.

 $Y=0.299 \times R(x',y')+0.587 \times G(x',y')+0.114 \times B(x',y')$ 

Cb=-0.169 x R(x',y')-0.331 x G(x',y')+0.5 x B(x',y')

 $YG=Y \times G(x,y)/G(x',y')$ 

b=YG+1.772 x Cb

wherein Y is a luminance value of said first similar pixel, R(x',y'), G(x',y'), and B(x',y') are said second R, first G, and second B-signals of said first similar pixel, G(x,y) is said second G-signal of said first objective pixel, b is said third B-signal obtained by said B-interpolation processor, and YG is said modified luminance value.

CUMENTLY AMENAED)

12. A device according to claim 2, wherein said R-interpolation processor obtains said third R-signal, using said color difference signal Cr and a modified luminance value which is obtained by multiplying said luminance value by a ratio of said second G-signal of said fourth objective pixel and said first G-signal of said second similar pixel.

(CHENEW PREPRED)

13. A device according to claim 12, wherein said R-interpolation processor obtains said third R-signal, according to the following formula.

 $Y=0.299 \times R(x',y')+0.587 \times G(x',y')+0.114 \times B(x',y')$   $Cr=0.5 \times R(x',y')-0.419 \times G(x',y')-0.081 \times B(x',y')$ 

 $YG=Y \times G(x,y)/G(x',y')$ 

20

r=YG+1.402 x Cr

wherein Y is a luminance value of said second similar pixel, R(x',y'), G(x',y'), and B(x',y') are said second R, first G, and second B-signals of said second similar pixel, G(x,y) is said second G-signal of said fourth objective

(

pixel, r is said third R-signal obtained by said R-interpolation processor, and YG is said modified luminance value.

(CHENEWILL BUENDOD)

15

14. A device according to claim 1, wherein said B-interpolation processor extracts said first similar pixel, using said first G-signal and said second R-signal of said pixels adjacent to said first objective pixel.

15. A device according to claim 1, wherein said R-interpolation processor extracts said second similar pixel, using said first G-signal and said second B-signal of said pixels adjacent to said fourth objective pixel.

16. A device according to claim 2, wherein said B-interpolation A processor obtains said third B-signal, using said color difference signal Cb and a modified luminance value which is obtained by multiplying said

luminance value by a ratio of a first reference value, which is obtained based on said second G-signal and said first R-signal of said first objective pixel, and a second reference value, which is obtained based on said first

G-signal and second R-signal of said first similar pixel. ( ധേമാലെ പുട്ടമാട് റ)

20 17. A device according to claim 16, wherein said B-interpolation processor obtains said third B-signal, according to the following formula.

 $Y=0.299 \times R(x',y')+0.587 \times G(x',y')+0.114 \times B(x',y')$ 

Cb=-0.169 x R(x',y')-0.331 x G(x',y')+0.5 x B(x',y')

YG=Y x

5

 $(0.587 \times G(x,y)+0.299 \times R(x,y))/(0.587 \times G(x',y')+0.299 \times R(x',y'))$ 

b=YG+1.772 x Cb

wherein Y is a luminance value of said first similar pixel, R(x',y'), G(x',y'), and B(x',y') are said second R, first G, and second B-signals of said first similar pixel, G(x,y) is said second G-signal of said first objective pixel, b is said third B-signal obtained by said B-interpolation processor, and YG is

said modified luminance value.

18. A device according to claim 2, wherein said R-interpolation processor obtains said third R-signal, using said color difference signal Cr and a modified luminance value which is obtained by multiplying said luminance value by a ratio of a first reference value, which is obtained based on said second G-signal and said first B-signal of said fourth objective pixel, and a second reference value, which is obtained based on

15 said first G-signal and said second B-signal of said second similar pixel.

19. A device according to claim 18, wherein said R-interpolation Processor obtains said third R-signal, according to the following formula.

 $Y=0.299 \times R(x',y')+0.587 \times G(x',y')+0.114 \times B(x',y')$ 

 $Cr=0.5 \times R(x',y')-0.419 \times G(x',y')-0.081 \times B(x',y')$ 

20 YG=Y.x

 $(0.587 \times G(x,y)+0.114 \times B(x,y))/(0.587 \times G(x',y')+0.114 \times B(x',y'))$ 

r=YG+1.402 x Cr

wherein Y is a luminance value of said second similar pixel, R(x',y'),

15

P21595.Claims

G(x',y'), and B(x',y') are said second R, first G, and second B-signals of said second similar pixel, G(x,y) is said second G-signal of said fourth objective pixel, r is said third R-signal obtained by said R-interpolation processor, and YG is said modified luminance value.

(CHORENTLY AMENDED)

20. A device according to claim 3, wherein said B-interpolation processor obtains said third B-signal, on the assumption that said color difference signals Cb and Cr of said first objective pixel are equal to said color difference signals Cb and Cr of said first similar pixel.

21. A device according to claim 3, wherein said R-interpolation processor obtains said third R-signal, on the assumption that said color difference signals Cb and Cr of said fourth objective pixel are equal to said color difference signals Cb and Cr of said second similar pixel.

(Curαξινίω Αμένικα)

22. A device according to claim 3, wherein said B-interpolation Λ

processor obtains said third B-signal, using said first R-signal of said first

objective pixel and said color difference signals Cb and Cr of said first similar pixel.

(山内尼川 八八 大以モロリン) 23. A device according to claim 22, wherein said B-interpolation 人 processor obtains said third B-signal, according to the following formula.

Cb=-0.169 x R(x',y')-0.331 x G(x',y')+0.5 x B(x',y')

20 Cr=0.5 x R(x',y')-0.419 x G(x',y')-0.081 x B(x',y')

b=1.293 x R(x,y)+2.293 x Cb-1.812 x Cr

wherein R(x',y'), G(x',y'), and B(x',y') are said second R, first G, and second B-signals of said first similar pixel, R(x,y) is said first R-signal of said first

objective pixel, and b is said third B-signal obtained by said B-interpolation processor.

(CHADELILY A MENDED)

24. A device according to claim 3, wherein said R-interpolation processor obtains said third R-signal, using said first B-signal of said

fourth objective pixel and said color difference signals Cb and Cr of said second similar pixel.

(ωνιτεμτικ Αμεωθεν)
25. A device according to claim 24, wherein said R-interpolation κ
processor obtains said third R-signal, according to the following formula.

Cb=-0.169 x R(x',y')-0.331 x G(x',y')+0.5 x B(x',y')

10 Cr=0.5 x R(x',y')-0.419 x G(x',y')-0.081 x B(x',y')

r=0.773 x B(x,y)-1.773 x Cb+1.401 x Cr

wherein R(x',y'), G(x',y'), and B(x',y') are said second R, first G, and second B-signals of said second similar pixel, B(x,y) is said first B-signal of said fourth objective pixel, r is said third R-signal obtained by said R-

15 interpolation processor.

Art Unit: 2615

2. Any inquiry concerning this communication or earlier communications from the examiner should be directed to TUAN HO whose telephone number is (703) 305-4943. The examiner can normally be reached on Mon-Fri from 7AM to 4PM.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's acting supervisor, Thai Tran can be reached on (703) 305-4725. The fax phone number for the organization where this application or proceeding is assigned is (703) 872-9306

Any inquiry of a general nature or relating to the status of this application or proceeding should be directed to the receptionist whose telephone number is (703) 305-4700.

TUAN HO

Primary Examiner

Art Unit 2615